

## 镇江太极电动车电源有限公司电池型号

GB (国标) 牵引用铅酸蓄电池											
型号 Type	5小时率 额定容量 5hr. Capacity (Ah)	最大外形尺寸(mm) Overall dimensions				参考重量5% Reference weight(kg)		容器材料 Material of container 槽/盖	极柱 数量	单体 电池 电压	备注
		长 L	宽 W	高 H	总高 H	无液 Dry	带液 Wet				
D-160	160	98	180	323	362	11	13	PP	2	2	
D-250B	250	138	180	290	331	13	17	pp	2	2	
D-250	250	140	210	290	331	13	17	pp	2	2	
D-330B	330	138	180	358	393	16	22	pp	2	2	
D-330	330	138	180	407	448	16	22.5	pp	2	2	
D-385	385	145	155	382	420	17.5	23.5	pp	2	2	
D-395	395	138	180	407	448	20	26	pp	2或4	2	
D-400	400	145	160	382	430	18	24	pp	2或4	2	
D-400	400	145	160	382	416	18	24	pp	2或4	2	焊接
D-440B	440	175	180	404	444	23	30	pp	4	2	
D-440B	440	175	180	404	439	23	30	pp	4	2	焊接
D-440	440	145	160	431	475	23	29	pp	2或4	2	
D-440	440	145	160	431	470	23	29	pp	2或4	2	焊接
D-440	440	145	160	445	480	23	29	pp	2或4	2	焊接
D-450	450	176	160	382	430	23.5	30.5	pp	4	2	
D-450	450	176	160	382	416	23.5	30.5	pp	4	2	焊接
D-480	480	145	160	431	475	24	31	pp	2或4	2	
D-480	480	145	160	445	480	24	31	pp	2或4	2	焊接
D-500	500	176	160	382	430	24.5	31.5	pp	4	2	
D-500	500	176	160	382	416	24.5	31.5	pp	4	2	焊接
D-515	515	175	180	404	444	26	33	pp	4	2	
D-515	515	175	180	404	439	26	33	pp	4	2	焊接
D-550	550	176	160	431	475	27	36	pp	4	2	
D-550	550	176	160	431	470	27	36	pp	4	2	焊接
D-580	580	176	160	431	475	27.5	36.5	pp	4	2	
D-580	580	176	160	431	470	27.5	36.5	pp	4	2	焊接
D-620	620	176	160	445	480	28	37	pp	4	2	
D-620	620	176	160	445	475	28	37	pp	4	2	焊接

主要用途：适用于电动叉车、搬运车、堆高车、托盘车、隧道/地铁机车、公路用车及其他深循环直流电源设备。本公司可根据用户要求设计研发新型蓄电池或配备自动注液系统。

Main uses: Applicable for electric forklifts, electric transporting cars, electric stacker cars, electric pallet trucks, tunnel / Metro locomotives, road vehicles and other deep-cycle DC power supply equipment. Our company can design new batteries and automatic liquid injection system according to the needs of users.

158宽VBS系列牵引用铅酸蓄电池

型号 Type	5小时率 额定容量 5hr. Capacity (Ah)	最大外形尺寸(mm) Overall dimensions				参考重量5% Reference weight(kg)		容器材料 Material of container 槽/盖	极柱 数量	单体电池 电压 (V)
		长 L	宽 W	高 H	总高 H	无液 Dry	带液 Wet			
2VBS80	80	45	158	330	365	3.7	4.9	PP	2	2
3VBS120	120	61	158	330	365	5.5	7.4	PP	2	2
4VBS160	160	77	158	330	365	7.4	9.8	PP	2	2
5VBS200	200	93	158	330	365	9.2	12.3	PP	2	2
6VBS240	240	109	158	330	365	11.0	14.7	PP	2或4	2
7VBS280	280	125	158	330	365	12.9	17.2	PP	2或4	2
8VBS320	320	141	158	330	365	14.7	19.6	PP	2或4	2
9VBS360	360	157	158	330	365	16.6	22.1	PP	2或4	2
10VBS400	400	173	158	330	365	18.4	24.5	PP	2或4	2
11VBS440	440	189	158	330	365	20.2	27.0	PP	4	2
12VBS480	480	205	158	330	365	22.1	29.5	PP	4	2
13VBS520	520	221	158	330	365	23.9	31.9	PP	4	2
14VBS560	560	237	158	330	365	25.8	34.4	PP	4	2
15VBS600	600	253	158	330	365	27.6	36.8	PP	4	2
2VBS100	100	45	158	385	420	4.6	6.1	PP	2	2
3VBS150	150	61	158	385	420	6.9	9.2	PP	2	2
4VBS200	200	77	158	385	420	9.2	12.3	PP	2	2
5VBS250	250	93	158	385	420	11.5	15.3	PP	2	2
6VBS300	300	109	158	385	420	13.8	18.4	PP	2或4	2
7VBS350	350	125	158	385	420	16.1	21.5	PP	2或4	2
8VBS400	400	141	158	385	420	18.4	24.5	PP	2或4	2
9VBS450	450	157	158	385	420	20.7	27.6	PP	2或4	2
10VBS500	500	173	158	385	420	23.0	30.7	PP	2或4	2
11VBS550	550	189	158	385	420	25.3	33.7	PP	4	2
12VBS600	600	205	158	385	420	27.6	36.8	PP	4	2
13VBS650	650	221	158	385	420	29.9	39.9	PP	4	2
14VBS700	700	237	158	385	420	32.2	43.0	PP	4	2
15VBS750	750	253	158	385	420	34.5	46.0	PP	4	2
2VBS110	110	45	158	400	435	5.1	6.7	PP	2	2
3VBS165	165	61	158	400	435	7.6	10.1	PP	2	2
4VBS220	220	77	158	400	435	10.1	13.5	PP	2	2
5VBS275	275	93	158	400	435	12.7	16.9	PP	2	2
6VBS330	330	109	158	400	435	15.2	20.2	PP	2或4	2
7VBS385	385	125	158	400	435	17.7	23.6	PP	2或4	2
8VBS440	440	141	158	400	435	20.2	27.0	PP	2或4	2
9VBS495	495	157	158	400	435	22.8	30.4	PP	2或4	2
10VBS550	550	173	158	400	435	25.3	33.7	PP	2或4	2
10VBS550H	550	173	158	400	435	25.3	33.7	PP	2或4	2
11VBS605	605	189	158	400	435	27.8	37.1	PP	4	2
12VBS660	660	205	158	400	435	30.4	40.5	PP	4	2

13VBS715	715	221	158	400	435	32.9	43.9	pp	4	2
14VBS770	770	237	158	400	435	35.4	47.2	pp	4	2
15VBS825	825	253	158	400	435	38.0	50.6	pp	4	2
2VBS120	120	45	158	431	465	5.5	7.4	pp	2	2
3VBS180	180	61	158	431	465	8.3	11.0	pp	2	2
4VBS240	240	77	158	431	465	11.0	14.7	pp	2	2
5VBS300	300	93	158	431	465	13.8	18.4	pp	2	2
6VBS360	360	109	158	431	465	16.6	22.1	pp	2或4	2
7VBS420	420	125	158	431	465	19.3	25.8	pp	2或4	2
8VBS480	480	141	158	431	465	22.1	29.5	pp	2或4	2
9VBS540	540	157	158	431	465	24.8	33.1	pp	2或4	2
10VBS600	600	173	158	431	465	27.6	36.8	pp	2或4	2
11VBS660	660	189	158	431	465	30.4	40.5	pp	4	2
12VBS720	720	205	158	431	465	33.1	44.2	pp	4	2
13VBS780	780	221	158	431	465	35.9	47.9	pp	4	2
14VBS840	840	237	158	431	465	38.6	51.5	pp	4	2
15VBS900	900	253	158	431	465	41.4	55.2	pp	4	2
2VBS130	130	45	158	460	495	6.0	8.0	pp	2	2
3VBS195	195	61	158	460	495	9.0	12.0	pp	2	2
4VBS260	260	77	158	460	495	12.0	16.0	pp	2	2
5VBS325	325	93	158	460	495	15.0	19.9	pp	2	2
6VBS390	390	109	158	460	495	17.9	23.9	pp	2或4	2
7VBS455	455	125	158	460	495	20.9	27.9	pp	2或4	2
8VBS520	520	141	158	460	495	23.9	31.9	pp	2或4	2
9VBS585	585	157	158	460	495	26.9	35.9	pp	2或4	2
10VBS650	650	173	158	460	495	29.9	39.9	pp	2或4	2
11VBS715	715	189	158	460	495	32.9	43.9	pp	4	2
12VBS780	780	205	158	460	495	35.9	47.9	pp	4	2
13VBS845	845	221	158	460	495	38.9	51.8	pp	4	2
14VBS910	910	237	158	460	495	41.9	55.8	pp	4	2
15VBS975	975	253	158	460	495	44.9	59.8	pp	4	2
2VBS140	140	45	158	495	525	6.4	8.6	pp	2	2
3VBS210	210	61	158	495	525	9.7	12.9	pp	2	2
4VBS280	280	77	158	495	525	12.9	17.2	pp	2	2
4VBS300H	300	89	158	495	525	13.8	18.4	pp	2	2
5VBS350	350	93	158	495	525	16.1	21.5	pp	2	2
6VBS420	420	109	158	495	525	19.3	25.8	pp	2或4	2
7VBS490	490	125	158	495	525	22.5	30.1	pp	2或4	2
8VBS560	560	141	158	495	525	25.8	34.4	pp	2或4	2
9VBS630	630	157	158	495	525	29.0	38.7	pp	2或4	2
10VBS700	700	173	158	495	525	32.2	43.0	pp	2或4	2
11VBS770	770	189	158	495	525	35.4	47.2	pp	4	2
12VBS840	840	205	158	495	525	38.6	51.5	pp	4	2
13VBS910	910	221	158	495	525	41.9	55.8	pp	4	2
14VBS980	980	237	158	495	525	45.1	60.1	pp	4	2
15VBS1050	1050	253	158	495	525	48.3	64.4	pp	4	2
2VBS160	160	45	158	525	560	7.4	9.8	pp	2	2

3VBS240	240	61	158	525	560	11.0	14.7	pp	2	2
4VBS320	320	77	158	525	560	14.7	19.6	pp	2	2
5VBS400	400	93	158	525	560	18.4	24.5	pp	2	2
6VBS480	480	109	158	525	560	22.1	29.5	pp	2或4	2
7VBS560	560	125	158	525	560	25.8	34.4	pp	2或4	2
8VBS640	640	141	158	525	560	29.4	39.3	pp	2或4	2
9VBS720	720	157	158	525	560	33.1	44.2	pp	2或4	2
10VBS800	800	173	158	525	560	36.8	49.1	pp	2或4	2
11VBS880	880	189	158	525	560	40.5	54.0	pp	4	2
12VBS960	960	205	158	525	560	44.2	58.9	pp	4	2
13VBS1040	1040	221	158	525	560	47.8	63.8	pp	4	2
14VBS1120	1120	237	158	525	560	51.5	68.7	pp	4	2
15VBS1200	1200	253	158	525	560	55.2	73.6	pp	4	2
2VBS180	180	45	158	600	635	8.3	11.0	pp	2	2
3VBS270	270	61	158	600	635	12.4	16.6	pp	2	2
4VBS360	360	77	158	600	635	16.6	22.1	pp	2	2
5VBS450	450	93	158	600	635	20.7	27.6	pp	2	2
6VBS540	540	109	158	600	635	24.8	33.1	pp	2或4	2
7VBS630	630	125	158	600	635	29.0	38.7	pp	2或4	2
8VBS720	720	141	158	600	635	33.1	44.2	pp	2或4	2
9VBS810	810	157	158	600	635	37.3	49.7	pp	2或4	2
10VBS900	900	173	158	600	635	41.4	55.2	pp	2或4	2
11VBS990	990	189	158	600	635	45.5	60.7	pp	4	2
12VBS1080	1080	205	158	600	635	49.7	66.3	pp	4	2
13VBS1170	1170	221	158	600	635	53.8	71.8	pp	4	2
14VBS1260	1260	237	158	600	635	58.0	77.3	pp	4	2
15VBS1350	1350	253	158	600	635	62.1	82.8	pp	4	2
2VBS200	200	45	158	690	720	9.2	12.3	pp	2	2
3VBS300	300	61	158	690	720	13.8	18.4	pp	2	2
4VBS400	400	77	158	690	720	18.4	24.5	pp	2	2
5VBS500	500	93	158	690	720	23.0	30.7	pp	2	2
6VBS600	600	109	158	690	720	27.6	36.8	pp	2或4	2
7VBS700	700	125	158	690	720	32.2	43.0	pp	2或4	2
8VBS800	800	141	158	690	720	36.8	49.1	pp	2或4	2
9VBS900	900	157	158	690	720	41.4	55.2	pp	2或4	2
10VBS1000	1000	173	158	690	720	46.0	61.4	pp	2或4	2
11VBS1100	1100	189	158	690	720	50.6	67.5	pp	4	2
12VBS1200	1200	205	158	690	720	55.2	73.6	pp	4	2
13VBS1300	1300	221	158	690	720	59.8	79.8	pp	4	2
14VBS1400	1400	237	158	690	720	64.4	85.9	pp	4	2
15VBS1500	1500	253	158	690	720	69.0	92.0	pp	4	2

主要用途：适用于电动叉车、搬运车、堆高车、托盘车、隧道/地铁机车、公路用车及其他深循环直流电源设备。  
本公司可根据用户要求设计研发新型蓄电池或配备自动注液系统。

Main uses:Applicable for electric forklifts, electric transporting cars , electric stacker cars, electric pallet trucks, tunnel / Metro locomotives, road vehicles and other deep-cycle DC power supply equipment.

Our company can design new batteries and automatic liquid injection system according to the needs of users.

### 198宽PZS系列牵引用铅酸蓄电池

型号 Type	5小时率 额定容量 5hr. Capacity (Ah)	最大外形尺寸(mm) Overall dimensions				参考重量5% Reference weight(kg)		容器材料 Material of container 槽/盖	极柱 数量	单体 电池 电压 (V)
		长 L	宽 W	高 H	总高 H	无液	带液			
2PzS120	120	47	198	360	390	5.5	7.4	pp	2	2
3PzS180	180	65	198	360	390	8.3	11.0	pp	2	2
4PzS240	240	83	198	360	390	11.0	14.7	pp	2	2
5PzS300	300	101	198	360	390	13.8	18.4	pp	2	2
6PzS360	360	119	198	360	390	16.6	22.1	pp	2	2
7PzS420	420	137	198	360	390	19.3	25.8	pp	2或4	2
8PzS480	480	155	198	360	390	22.1	29.5	pp	2或4	2
9PzS540	540	173	198	360	390	24.8	33.1	pp	2或4	2
10PzS600	600	191	198	360	390	27.6	36.8	pp	2或4	2
12PzS720	720	227	198	360	390	33.1	44.2	pp	4	2
2PzS140	140	47	198	405	435	6.4	8.6	pp	2	2
3PzS210	210	65	198	405	435	9.7	12.9	pp	2	2
4PzS280	280	83	198	405	435	12.9	17.2	pp	2	2
5PzS350	350	101	198	405	435	16.1	21.5	pp	2	2
6PzS420	420	119	198	405	435	19.3	25.8	pp	2	2
7PzS490	490	137	198	405	435	22.5	30.1	pp	2或4	2
8PzS560	560	155	198	405	435	25.8	34.4	pp	2或4	2
9PzS630	630	173	198	405	435	29.0	38.7	pp	2或4	2
10PzS700	700	191	198	405	435	32.2	43.0	pp	2或4	2
12PzS840	840	227	198	405	435	38.6	51.5	pp	4	2
2PzS160	160	47	198	430	465	7.4	9.8	pp	2	2
3PzS240	240	65	198	430	465	11.0	14.7	pp	2	2
4PzS320	320	83	198	430	465	14.7	19.6	pp	2	2
5PzS400	400	101	198	430	465	18.4	24.5	pp	2	2
6PzS480	480	119	198	430	465	22.1	29.5	pp	2	2
7PzS560	560	137	198	430	465	25.8	34.4	pp	2或4	2
8PzS640	640	155	198	430	465	29.4	39.3	pp	2或4	2
9PzS720	720	173	198	430	465	33.1	44.2	pp	2或4	2
10PzS800	800	191	198	430	465	36.8	49.1	pp	2或4	2
12PzS960	960	227	198	430	465	44.2	58.9	pp	4	2
2PzS180	180	47	198	500	535	8.3	11.0	pp	2	2
3PzS270	270	65	198	500	535	12.4	16.6	pp	2	2
4PzS360	360	83	198	500	535	16.6	22.1	pp	2	2
5PzS450	450	101	198	500	535	20.7	27.6	pp	2	2
6PzS540	540	119	198	500	535	24.8	33.1	pp	2	2
7PzS630	630	137	198	500	535	29.0	38.7	pp	2或4	2
8PzS720	720	155	198	500	535	33.1	44.2	pp	2或4	2
9PzS810	810	173	198	500	535	37.3	49.7	pp	2或4	2
10PzS900	900	191	198	500	535	41.4	55.2	pp	2或4	2

12PzS1080	1080	227	198	500	535	49.7	66.3	pp	4	2
2PzS200	200	47	198	525	560	9.2	12.27	pp	2	2
3PzS300	300	65	198	525	560	13.8	18.4	pp	2	2
4PzS400	400	83	198	525	560	18.4	24.5	pp	2	2
5PzS500	500	101	198	525	560	23.0	30.7	pp	2	2
6PzS600	600	119	198	525	560	27.6	36.8	pp	2	2
7PzS700	700	137	198	525	560	32.2	43.0	pp	2或4	2
8PzS800	800	155	198	525	560	36.8	49.1	pp	2或4	2
9PzS900	900	173	198	525	560	41.4	55.2	pp	2或4	2
10PzS1000	1000	191	198	525	560	46.0	61.4	pp	2或4	2
12PzS1200	1200	227	198	525	560	55.2	73.6	pp	4	2
2PzS230	230	47	198	545	575	10.6	14.1	pp	2	2
3PzS345	345	65	198	545	575	15.9	21.2	pp	2	2
4PzS460	460	83	198	545	575	21.2	28.2	pp	2	2
5PzS575	575	101	198	545	575	26.5	35.3	pp	2	2
6PzS690	690	119	198	545	575	31.7	42.3	pp	2	2
7PzS805	805	137	198	545	575	37.0	49.4	pp	2或4	2
8PzS920	920	155	198	545	575	42.3	56.5	pp	2或4	2
9PzS1035	1035	173	198	545	575	47.6	63.5	pp	2或4	2
10PzS1150	1150	191	198	545	575	52.9	70.6	pp	2或4	2
12PzS1380	1380	227	198	545	575	63.5	84.7	pp	4	2
2PzS240	240	47	198	570	600	11.0	14.7	pp	2	2
3PzS360	360	65	198	570	600	16.6	22.1	pp	2	2
4PzS480	480	83	198	570	600	22.1	29.5	pp	2	2
5PzS600	600	101	198	570	600	27.6	36.8	pp	2	2
6PzS720	720	119	198	570	600	33.1	44.2	pp	2	2
7PzS840	840	137	198	570	600	38.6	51.5	pp	2或4	2
8PzS960	960	155	198	570	600	44.2	58.9	pp	2或4	2
9PzS1080	1080	173	198	570	600	49.7	66.3	pp	2或4	2
10PzS1200	1200	191	198	570	600	55.2	73.6	pp	2或4	2
12PzS1440	1440	227	198	570	600	66.2	88.4	pp	4	2
4PzS460H	460	83	198	690	720	22.0	30.0	pp	2	2
2PzS250	250	47	198	600	630	11.5	15.3	pp	2	2
3PzS375	375	65	198	600	630	17.3	23.0	pp	2	2
4PzS500	500	83	198	600	630	23.0	30.7	pp	2	2
5PzS625	625	101	198	600	630	28.8	38.4	pp	2	2
6PzS750	750	119	198	600	630	34.5	46.0	pp	2	2
7PzS875	875	137	198	600	630	40.3	53.7	pp	2或4	2
8PzS1000	1000	155	198	600	630	46.0	61.4	pp	2或4	2
9PzS1125	1125	173	198	600	630	51.8	69.0	pp	2或4	2
10PzS1250	1250	191	198	600	630	57.5	76.7	pp	2或4	2
12PzS1500	1500	227	198	600	630	69.0	92.0	pp	4	2
2PzS270	270	47	198	670	700	12.4	16.6	pp	2	2
3PzS405	405	65	198	670	700	18.6	24.9	pp	2	2
4PzS540	540	83	198	670	700	24.8	33.1	pp	2	2
5PzS675	675	101	198	670	700	31.1	41.4	pp	2	2
6PzS810	810	119	198	670	700	37.3	49.7	pp	2	2

7PzS945	945	137	198	670	700	43.5	58.0	pp	2或4	2
8PzS1080	1080	155	198	670	700	49.7	66.3	pp	2或4	2
9PzS1215	1215	173	198	670	700	55.9	74.6	pp	2或4	2
10PzS1350	1350	191	198	670	700	62.1	82.8	pp	2或4	2
12PzS1620	1620	227	198	670	700	74.5	99.4	pp	4	2
2PzS280	280	47	198	690	720	12.9	17.2	pp	2	2
3PzS420	420	65	198	690	720	19.3	25.8	pp	2	2
4PzS560	560	83	198	690	720	25.8	34.4	pp	2	2
5PzS700	700	101	198	690	720	32.2	43.0	pp	2	2
6PzS840	840	119	198	690	720	38.6	51.5	pp	2	2
7PzS980	980	137	198	690	720	45.1	60.1	pp	2或4	2
8PzS1120	1120	155	198	690	720	51.5	68.7	pp	2或4	2
9PzS1260	1260	173	198	690	720	58.0	77.3	pp	2或4	2
10PzS1400	1400	191	198	690	720	64.4	85.9	pp	2或4	2
12PzS1680	1680	227	198	690	720	77.3	103.1	pp	4	2
2PzS310	310	47	198	720	750	14.3	19.0	pp	2	2
3PzS465	465	65	198	720	750	21.4	28.5	pp	2	2
4PzS620	620	83	198	720	750	28.5	38.0	pp	2	2
5PzS775	775	101	198	720	750	35.7	47.6	pp	2	2
6PzS930	930	119	198	720	750	42.8	57.1	pp	2	2
7PzS1085	1085	137	198	720	750	49.9	66.6	pp	2或4	2
8PzS1240	1240	155	198	720	750	57.0	76.1	pp	2或4	2
9PzS1395	1395	173	198	720	750	64.2	85.6	pp	2或4	2
10PzS1550	1550	191	198	720	750	71.3	95.1	pp	2或4	2
12PzS1860	1860	227	198	720	750	85.6	114.1	pp	4	2

主要用途：适用于电动叉车、搬运车、堆高车、托盘车、隧道/地铁机车、公路用车及其他深循环直流电源设备。  
本公司可根据用户要求设计研发新型蓄电池或配备自动注液系统。

Main uses:Applicable for electric forklifts, electric transporting cars , electric stacker cars, electric pallet trucks, tunnel / Metro locomotives, road vehicles and other deep-cycle DC power supply equipment.

Our company can design new batteries and automatic liquid injection system according to the needs of users.

## 电动车用铅酸蓄电池

型号	5小时额定容量(AH)	电压(V)	最大外形尺寸(MM)				电池重量(Kg)	
			长	宽	高	总高	干重	湿重
3-D-180	180	6	260	180	245	288	21	27
3-D-190	190	6	245	190	252	288	22	30
3-D-210	210	6	245	190	252	288	23	30
3-D-210A	210	6	260	180	288	313	24	32
3-D-220	220	6	245	190	282	318	25	35
3-D-250	250	6	245	190	282	318	27	35
3-D-260	260	6	360	172	275	292	29	38
4-D-135	135	8	260	180	245	288	21	27
3-EVF-200	200	6	260	180	270	270	36	36
3-EVF-200A	200	6	260	180	270	270	36	36
4-EVF-150	150	8	260	180	280	280	36	36
4-EVF-165	165	8	260	180	280	280	36.5	36.5
6-EVF-22	22	12	181	77	170	170	6.9	6.9
6-EVF-42	42	12	223	106	173	173	11.9	11.9
6-EVF-48	48	12	224	121	176	176	13.5	13.5
6-EVF-52	52	12	224	135	176	176	15	15
6-EVF-58	58	12	224	150	177	177	16.8	16.8
6-EVF-75	75	12	259	168	215	215	24	24
6-EVF-85	85	12	259	168	215	215	26	26
6-EVF-100	100	12	330	170	215	235	33.4	33.4
6-EVF-110	110	12	330	172	215	215	34	34
6-EVF-120	120	12	400	172	210	230	41	41
6-EVF-125A	125	12	405	174	213	216	41	41
6-EVF-125B	125	12	402	170	240	243	42	42
6-EVF-125C	125	12	303	181	264	267	44	44
6-EVF-150A	150	12	482	170	240	240	52	52
6-EVF-150B	150	12	340	180	264	267	54	54

主要用途：适用于电动游览车、高尔夫球车、电动游船（艇）、清扫环卫车、电动搬运车、堆高车、电动汽车等，并可作为其他移动设备的直流电源。

本公司可根据用户要求设计研发新型蓄电池。

Main uses: Applicable for electric tour buses, golf carts, electric boats, cleaning sanitation trucks, electric stacker cars, electric pallet trucks, electric vehicles, and other mobile devices as a DC power.

Our company can design new batteries according to the needs of users.